



PUSTEFIX GmbH Kilchberg, Bahnhofstraße 29 72072 Tübingen	Tel. 07071 - 791005 Fax 07071 - 791007 info@pustefix-promotion.de	 www.pustefix-promotion.de
TECHNICAL SPECIFICATIONS Label Printing		

as per: 01.02.2022
page: 1/2

Safety	<p>Many PUSTEFIX toys are marked with the "spiel gut" ("play well") label, all products fulfill all requirements of the EN71 for the safety of toys. Such safety is guaranteed by the producer. Pursuant to the provisions the toys are to be labeled with the standardized, at least 5mm high CE emblem and with the user instruction: "WARNING! Not suitable for children under 36 months. Choking hazard due to swallowable liquid". In addition all consumer products need to be marked with the producer name and mail address. This can be your clients information as well as your or our information. Due to the individual printing the labeling has to be considered in the customer's layout.</p> <p>The contractor guarantees the copyrights to the motive used and shall be liable for compliance with the legal provisions.</p>
--------	---


Material	White-high gloss-sensitive pressure paper 80 g/qm, wood-free.		
Gumming	Strongly adhesive.		
Format	label	Small Tube	Height x Circumference 85,0 x 99,0 mm
		Large Tube	Height x Circumference 95,0 x 124,0 mm
	print data incl. 1,5 mm trimming on each side	Small Tube	Height x Circumference 88,0 x 102,0 mm
		Large Tube	Height x Circumference 98,0 x 127,0 mm
Form	Rectangle.		
Features	With varnish.		
Presentation	On roller. Core diameter min. Outer diameter max. Label spacing min. Label spacing max.	76.0 mm 260.0 mm 3.0 mm 4.4 mm	
Arrangement	Labels arranged lengthwise.		
Winding	left ahead, outside.		

Data transmission up to max. 10 MB	via e-mail in PDF format	
Data	QuarkXPress 9.5 Photoshop CC Illustrator CC Corel Draw 12.0 Indesign CC	MAC / PC MAC / PC MAC / PC PC MAC
	Open-format data with all corresponding fonts and images or EPS files with fonts converted into curves and the corresponding images.	
Images	Please save all images for scale printing CMYK, no RGB. Images must always be inserted 1:1 into data. Use min. 300 dpi images.	
Colors	No RGB colors, do not set up black in CMYK.	
Reverse Script	As far as possible, only use single-colored background for reverse script. Do not use serif or script fonts. Font size min. 10 pt.	



TECHNICAL SPECIFICATIONS
Label Printing

as per: 01.02.2022
page: 2/2



small tube overlap area – 5 mm

large tube overlap area – 9 mm